

Application No. 09/328,939
Amendment dated January 26, 2004
Reply to Office Action of July 25, 2003

PATENT

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of surface treatment in a substantially downstream position of a plasma source to substantially be free from an undesirable influence of a reactive species from the plasma source, where an object to be processed is downstream from the plasma source, the method comprising generating a plasma discharge including a gas-C, the gas-C comprising a Gas-A molecule including essentially hydrogen as an element and a Gas-B including essentially $[[a]]$ a halide; wherein said plasma discharge is substantially free from an oxygen bearing species; and wherein the Gas B is selected from hydrogen chloride or hydrogen bromide; wherein Gas C comprises a flow rate defined as a ratio of an amount of hydrogen in Gas-B to that in Gas-A is larger than 1/480.

2. (Original) The method of claim 1 further comprising injecting a Gas-D in the downstream of the plasma of Gas-C to treat the object comprising a surface in a downstream position of the Gas-D injection.

3. (Canceled)

4. (Canceled)

5. (Previously Presented) The method of claim 1, wherein Gas-B does not contain an oxygen atom.

6. (Canceled)

7. (Canceled)

8. (Canceled)

Application No. 09/328,939
Amendment dated January 26, 2004
Reply to Office Action of July 25, 2003

PATENT

9. (Original) The method of claim 2, wherein gas containing silicon as its element is used as Gas-D.

10. (Original) The method of claim 2, wherein gas containing carbon as its element is used as Gas-D.

11. (Original) The method of claim 2, wherein gas containing fluorine as its element is used as Gas-D.

12. to 20. (Canceled)

21. (Original) The method of claim 1 wherein the method is provided to substantially prevent physical damage caused by a high energy particle.

22. (Canceled)

23. (Currently Amended) A method of surface treatment in a substantially downstream position of a plasma source, where an object to be processed is downstream from the plasma source, the method comprising generating a plasma discharge including a gas-C, the gas-C comprising a Gas-A molecule including essentially hydrogen as an element and a Gas-B including ~~essentially a halogen and a hydrogen-bearing species~~; wherein said plasma discharge is substantially free from an oxygen bearing species; and wherein the Gas B is selected from at least a chlorine, bromine, iodine, or fluorine; wherein Gas C comprises a flow rate defined as a ratio of an amount of hydrogen in Gas-B to that in Gas-A is larger than 1/480.

24. (Previously Presented) The method of claim 23 further comprising injecting a Gas-D in the downstream of the plasma of Gas-C to treat the object comprising a surface in a downstream position of the Gas-D injection.

25. (Previously Presented) The method of claim 23 wherein Gas-B does not contain an oxygen atom.

Application No. 09/328,939
Amendment dated January 26, 2004
Reply to Office Action of July 25, 2003

PATENT

26. (Previously Presented) The method of claim 23 wherein gas containing silicon as its element is used as Gas-D.

27. (Previously Presented) The method of claim 23 wherein gas containing carbon as its element is used as Gas-D.

28. (Previously Presented) The method of claim 23 wherein gas containing fluorine as its element is used as Gas-D.

29. (Previously Presented) The method of claim 23 wherein the method is provided to substantially prevent physical damage caused by a high energy particle.